

# Chapter 33

---

## ■ Estimation for Software Projects

*Slide Set to accompany*

*Software Engineering: A Practitioner's Approach, 8/e*

**by Roger S. Pressman and Bruce R. Maxim**

**Slides copyright © 1996, 2001, 2005, 2009, 2014 by Roger S. Pressman**

***For non-profit educational use only***

May be reproduced ONLY for student use at the university level when used in conjunction with *Software Engineering: A Practitioner's Approach, 8/e*. Any other reproduction or use is prohibited without the express written permission of the author.

All copyright information MUST appear if these slides are posted on a website for student use.

# Software Project Planning

The overall goal of project planning is to establish a pragmatic strategy for controlling, tracking, and monitoring a complex technical project.

Why?

*So the end result gets done on time, with quality!*

# Project Planning Task Set-I

---

- Establish project scope
- Determine feasibility
- Analyze risks
  - Risk analysis is considered in detail in Chapter 25.
- Define required resources
  - Determine require human resources
  - Define reusable software resources
  - Identify environmental resources

# Project Planning Task Set-II

---

- Estimate cost and effort
  - Decompose the problem
  - Develop two or more estimates using size, function points, process tasks or use-cases
  - Reconcile the estimates
- Develop a project schedule
  - Scheduling is considered in detail in Chapter 34.
    - Establish a meaningful task set
    - Define a task network
    - Use scheduling tools to develop a timeline chart
    - Define schedule tracking mechanisms


# Estimation

---

- Estimation of resources, cost, and schedule for a software engineering effort requires
  - experience
  - access to good historical information (metrics)
  - the courage to commit to quantitative predictions when qualitative information is all that exists
- Estimation carries inherent risk and this risk leads to uncertainty

# Write it Down!

---



# To Understand Scope ...

---

- Understand the customers needs
- understand the business context
- understand the project boundaries
- understand the customer's motivation
- understand the likely paths for change
- understand that ...

***Even when you understand,  
nothing is guaranteed!***


# What is Scope?

---

- *Software scope* describes
  - the functions and features that are to be delivered to end-users
  - the data that are input and output
  - the “content” that is presented to users as a consequence of using the software
  - the performance, constraints, interfaces, and reliability that *bound* the system.
- Scope is defined using one of two techniques:
  - A narrative description of software scope is developed after communication with all stakeholders.
  - A set of use-cases is developed by end-users.



# Resources



# Project Estimation

---




- Project scope must be understood
- Elaboration (decomposition) is necessary
- Historical metrics are very helpful
- At least two different techniques should be used
- Uncertainty is inherent in the process

# Estimation Techniques

---

- Past (similar) project experience
- Conventional estimation techniques
  - task breakdown and effort estimates
  - size (e.g., FP) estimates
- Empirical models
- Automated tools




# Estimation Accuracy

---

- Predicated on ...
  - the degree to which the planner has properly estimated the size of the product to be built
  - the **ability to translate** the size estimate into human effort, calendar time, and dollars (a function of the availability of reliable software metrics from past projects)
  - the degree to which the project plan reflects the **abilities of the software team**
  - the **stability of product requirements** and the environment that supports the software engineering effort.

# Functional Decomposition



# Conventional Methods: LOC/FP Approach

---

- compute LOC/FP using estimates of information domain values
- use historical data to build estimates for the project

# Example: LOC Approach

Function	Estimated LOC
user interface and control facilities (UICF)	2,300
two-dimensional geometric analysis (2D GA)	8,300
three-dimensional geometric analysis (3D GA)	6,800
database management (DBM)	3,380
computer graphics display facilities (CGDF)	4,980
peripheral control (PC)	2,100
design analysis modules (DAM)	8,400
<i>estimated lines of code</i>	<b>33,200</b>

Average productivity for systems of this type = 620 LOC/pm.

Burdened labor rate = \$8000 per month, the cost per line of code is approximately \$13.

Based on the LOC estimate and the historical productivity data, the total estimated project cost is **\$431,000 and the estimated effort is 54 person-months.**

# Example: FP Approach

Information Domain Value	opt.	likely	poss.	est. count	weight	FP-count
number of inputs	20	24	30	24	4	97
number of outputs	12	15	22	16	5	78
number of inquiries	16	22	28	22	5	88
number of files	4	4	5	4	10	42
number of external interfaces	2	2	3	2	7	15
<b>count-total</b>						<b>321</b>

The estimated number of FP is derived:

$$FP_{\text{estimated}} = \text{count-total} \cdot 3 [0.65 + 0.01 \cdot 3 S (F_i)]$$

$$FP_{\text{estimated}} = 375$$

organizational average productivity = 6.5 FP/pm.


burdened labor rate = \$8000 per month, approximately \$1230/FP.

Based on the FP estimate and the historical productivity data, **total estimated project cost is \$461,000 and estimated effort is 58 person-months.**



# Process-Based Estimation

Obtained from “process framework”



# Process-Based Estimation Example

Activity →	CC	Planning	Risk Analysis	Engineering		Construction Release		CE	Totals
Task →				analysis	design	code	test		
Function ▼									
UICF				0.50	2.50	0.40	5.00	n/a	8.40
2DGA				0.75	4.00	0.60	2.00	n/a	7.35
3DGA				0.50	4.00	1.00	3.00	n/a	8.50
CGDF				0.50	3.00	1.00	1.50	n/a	6.00
DSM				0.50	3.00	0.75	1.50	n/a	5.75
PCF				0.25	2.00	0.50	1.50	n/a	4.25
DAM				0.50	2.00	0.50	2.00	n/a	5.00
<b>Totals</b>	0.25	0.25	0.25	3.50	20.50	4.50	16.50		46.00
<b>% effort</b>	1%	1%	1%	8%	45%	10%	36%		

CC = customer communication CE = customer evaluation

Based on an average burdened labor rate of \$8,000 per month, **the total estimated project cost is \$368,000 and the estimated effort is 46 person-months.**

# Tool-Based Estimation

---


**project characteristics**



**calibration factors**



**LOC/FP data**




# Estimation with Use-Cases

	use cases	scenarios	pages	scenarios	pages	LOC	LOC estimate
User interface subsystem	6	10	6	12	5	560	3,366
Engineering subsystem group	10	20	8	16	8	3100	31,233
Infrastructure subsystem group	5	6	5	10	6	1650	7,970
Total LOC estimate							42,568

Using 620 LOC/pm as the average productivity for systems of this type and a burdened labor rate of \$8000 per month, the cost per line of code is approximately \$13. Based on the use-case estimate and the historical productivity data, **the total estimated project cost is \$552,000 and the estimated effort is 68 person-months.**

# Empirical Estimation Models

**General form:**



# COCOMO-II

---

- COCOMO II is actually a hierarchy of estimation models that address the following areas:
  - *Application composition model*. Used during the early stages of software engineering, when prototyping of user interfaces, consideration of software and system interaction, assessment of performance, and evaluation of technology maturity are paramount.
  - *Early design stage model*. Used once requirements have been stabilized and basic software architecture has been established.
  - *Post-architecture-stage model*. Used during the construction of the software.

# The Software Equation

---

*A dynamic multivariable model*

$$E = [\text{LOC} \times B^{0.333}/P]^3 \times (1/t^4)$$

where

E = effort in person-months or person-years

t = project duration in months or years

B = “special skills factor”

P = “productivity parameter”

# Estimation for OO Projects-I

---

- Develop estimates using effort decomposition, FP analysis, and any other method that is applicable for conventional applications.
- Using object-oriented requirements modeling (Chapter 6), develop use-cases and determine a count.
- From the analysis model, determine the number of key classes (called analysis classes in Chapter 6).
- Categorize the type of interface for the application and develop a multiplier for support classes:

<b>Interface type</b>	<b>Multiplier</b>
■ No GUI	2.0
■ Text-based user interface	2.25
■ GUI	2.5
■ Complex GUI	3.0



# Estimation for OO Projects-II

---


- Multiply the number of key classes (step 3) by the multiplier to obtain an estimate for the number of support classes.
- Multiply the total number of classes (key + support) by the average number of work-units per class. Lorenz and Kidd suggest 15 to 20 person-days per class.
- Cross check the class-based estimate by multiplying the average number of work-units per use-case

# Estimation for Agile Projects

---

- Each user scenario (a mini-use-case) is considered separately for estimation purposes.
- The scenario is decomposed into the set of software engineering tasks that will be required to develop it.
- Each task is estimated separately. Note: estimation can be based on historical data, an empirical model, or “experience.”
  - Alternatively, the ‘volume’ of the scenario can be estimated in LOC, FP or some other volume-oriented measure (e.g., use-case count).
- Estimates for each task are summed to create an estimate for the scenario.
  - Alternatively, the volume estimate for the scenario is translated into effort using historical data.
- The effort estimates for all scenarios that are to be implemented for a given software increment are summed to develop the effort estimate for the increment.

# The Make-Buy Decision



# Computing Expected Cost

expected cost =

$$\sum_i (\text{path probability})_i \times (\text{estimated path cost})_i$$

*For example, the expected cost to build is:*

$$\begin{aligned} \text{expected cost}_{\text{build}} &= 0.30 (\$380\text{K}) + 0.70 (\$450\text{K}) \\ &= \$429 \text{ K} \end{aligned}$$

*similarly,*

$$\text{expected cost}_{\text{reuse}} = \$382\text{K}$$

$$\text{expected cost}_{\text{buy}} = \$267\text{K}$$

$$\text{expected cost}_{\text{contr}} = \$410\text{K}$$